



➤ RATEC program



➤ Shuttering magnets



➤ Shuttering systems



➤ RATEC Battery System



➤ Inserts & Insert Magnets



➤ Special shuttering



➤ Upcrete® Pump Station

Technical changes reserved | www.bloesch-partner.de 4/13

Fast and economical shuttering adapter

It isn't possible to fix shuttering elements in a more efficient way!

RATEC

Meet the better ideas!

Headquarters Germany
RATEC GmbH
Karlsruher Strasse 32
D-68766 Hockenheim
Phone +49-6205-9407-29
Fax +49-6205-9407-30
info@ratec.org
www.ratec.org

Headquarters America
RATEC LLC
6003 126th Ave North
Clearwater, FL 33760
Phone +1-727-363-7732
Fax +1-727-363-7463
infoUS@ratec.org
www.ratec.org

www.ratec.org

RATEC
Meet the better ideas!

➤ Economical shuttering adapter for EURO RTM standard magnets



➤ **Universal Adapter H set:**

Universal adapter incl. EURO RTM 250-900 for completely adjustable, right-edged fixing of wood shutterings

Height: 240 mm	Art. No. 10696
Height: 300 mm	Art. No. 02724
Height: 350 mm	Art. No. 10805
Height: 400 mm	Art. No. 07412



➤ **Universal Adapter GF set:**

Universal adapter incl. EURO RTM 250-900 for completely adjustable, right-edged fixing of concrete upstand, „Schalbord“, stop end, stop elements ASE.

Height: 240 mm	Art. No. 10714
Height: 300 mm	Art. No. 08239
Height: 350 mm	Art. No. 10713
Height: 400 mm	Art. No. 07764



➤ **Lifting tool**

Art. No. 00204

➤ Universal adapter and EURO RTM 250-900 are available individual

➤ SPEEDY. Fast shuttering adapter for shuttering wood and fibreglass upstand.



➤ **SPEEDY-adapter H**

for completely adjustable, right-angled fixing of „betonplan“, „Doka“ and wood.

up to height 400 mm Art. No. 03118



➤ **SPEEDY-adapter GF**

for completely adjustable, right-angled fixing of concrete upstand, „Schalbord“, stop end, stop elements ASE.

up to height 400 mm Art. No. 02858



➤ **Lifting tool SPEEDY**

Art. No. 02860



➤ Because of the integrated Pro magnet, the system stays cleaner and allows for a fast and easy clean up. Recesses like windows and doors out of wood, plastic, steel and fibre concrete can be easily and exactly moved and adjusted.



Magnet deactivated - adjust adapter



Magnet activated - adapter fixed



Longitudinal positioning of shuttering...



...or positioning shuttering 135°...



...or positioning shuttering 90° right-edged



fixation holder - ready